



## Neotex<sup>®</sup> 1080

## Special thinner for primers and coatings

## Description

Special thinner suitable for the vinyl resin primer **Vinyfix® Primer**, as well as for the acrylic resin coating **Betofix® Waterstop**.

Also suitable for the cleaning of the surfaces or tools after the application of the above products.



Packing

Technical Characteristics	
Density (EN ISO 2811-1)	0,87kg/L (±0,05)
Appearance	Transparent
Packing	1L in metal cans
UFI code	WY90-Y0AF-E00J-JPCK
Storage stability	2 years, stored in its original sealed packing, protected from frost, humidity and exposure to sunlight

The information supplied in this datasheet, concerning the uses and the applications of the product, is based on the experience and knowledge of NEOTEX\* SA. It is offered as a service to designers and contractors to help them find potential solutions. However, as a supplier, NEOTEX\* SA does not control the actual use of the product and therefore cannot be held responsible for the results of its use. As a result of continual technical evolution, it is up to our clients to check with our technical department that this present data sheet has not been modified by a more recent edition

HEADQUARTERS - PLANT V. Moira str., Xiropigado LOGISTICS SALES & CENTER Loutsas str., Voro

P.O. Box 2315, GR 19600 Industrial Area Mandra Athens, Greece **T.** +30 210 5557579

## NORTHERN GREECE BRANCH

Ionias str., GR 57009 Kalochori, Thessaloniki, Greece **T.** +30 2310 467275