

HEADQUARTERS - PLANT
V. Moira str., Xiropigado
LOGISTICS & SALES CENTER
Loutsas str., Voro

P.O. Box 2315, GR 19600 Industrial Area Mandra Athens, Greece T. +30 210 5557579

NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece T. +30 2310 467275

 $www.neotex.gr \bullet export@neotex.gr$

CONSTRUCTION CHEMICALS SINCE 1959

Declaration of Performance - DoP No.: 4950-77

Neopox[®] Special Primer 1225



1.	Unique identification code of the product type:	Neopox® Special Primer 1225
2.	Intended use/es:	Reinforcement corrosion protection
3.	Manufacturer:	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece
4.	Authorized representative:	
5.	System/s of Assessment and Verification of Constancy of Performance (AVCP):	2+
6a.	Harmonized standard	EN 1504-7
	Notified body/ies:	The notified body, DEDAL Attestation & Certification, Bulgaria, 8230 Nesebar Mladost #50, with certification no. 1922, carried out the initial inspection of the factory and the production control at the factory and conducts continuous monitoring, evaluation, and approval of the production control under system 2+ and issued: Certificate of Conformity of the production control at the factory No. 1922-CPR-0386
6b.	European assessment document:	
	European technical assessment:	
	Technical assessment body:	
	Notified body/ies:	



CONSTRUCTION CHEMICALS SINCE 1959

HEADQUARTERS - PLANT
V. Moira str., Xiropigado
LOGISTICS & SALES CENTER
Loutsas str., Voro

P.O. Box 2315, GR 19600 Industrial Area Mandra Athens, Greece T. +30 210 5557579

NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece T. +30 2310 467275

www.neotex.gr • export@neotex.gr

Declaration of Performance - DoP No.: 4950-77

Neopox[®] Special Primer 1225



7. Declared performance/s:

Essenti	al characteristics	Performance	Harmonized technical specification
Corrosi	on protection	Pass	
Glass tr	ansition temperature	>+40°C	
Shear a	adhesion of coated steel to	Pass	EN 1504-7
Danger	ous substances	Complies with 5.3	

8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX AEVE

BRANCH: LOUTSAS STR., THESI VORO, 19600, INDUSTRIAL AREA MANDRA GREECE HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA GREECE TEL.: +302105557578 - +302105246826 - FAX: +302105558482 VAT: EL 094029045 - PRN: 4164 www.neotex.gr e-mail: export@neotex.gr

Lampros Ntoumos

Technical Director

BRANCH: LOUISAS STR, THESI VORO., 19601 - NDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA GREECE
TEL.: +302105557579 - +302105246826 - FAX: +302105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Marios Bougiouk-Ioannidis

R&D Director



CONSTRUCTION CHEMICALS SINCE 1959

HEADQUARTERS - PLANT V. Moira str., Xiropigado LOGISTICS & SALES CENTER Loutsas str., Voro

P.O. Box 2315, GR 19600 | NORTHERN GREECE BRANCH Industrial Area Mandra Athens, Greece **T.** +30 210 5557579

Ionias str., GR 57009 Kalochori Thessaloniki, Greece **T.** +30 2310 467275

www.neotex.gr • export@neotex.gr



1922

NEOTEX S.A.

V.Moira str., P.O. Box 2315 GR 19600 Industrial Area Mandra, Athens, Greece

22

1922-CPR-0386

DoP No.: 4950-77

EN 1504-7

Neopox® Special Primer 1225

Reinforcement corrosion protection

Corrosion protection	Pass	
Glass transition temperature	>+40°C	
Shear adhesion of coated steel to	Pass	
concrete		
Dangerous substances	Complies with 5.3	

Declarations of Performance (DoPs)



