

**CONSTRUCTION CHEMICALS SINCE 1959** 

**HEADQUARTERS - PLANT** V. Moira str., Xiropigado LOGISTICS & SALES CENTER Loutsas str., Voro

Industrial Area Mandra Athens, Greece T. +30 210 5557579

P.O. Box 2315, GR 19600 | NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece **T.** +30 2310 467275

www.neotex.gr • export@neotex.gr

## Declaration of Performance - DoP No.: 4950-12

# Silatex<sup>®</sup> Super

( (

1.	Unique identification code of the product type:	Silatex <sup>®</sup> Super
2.	Intended use/es:	Surface protection products - Coating
3.	Manufacturer:	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece
4.	Authorized representative:	
5.	System/s of Assessment and Verification of Constancy of Performance (AVCP):	2+
6a.	Harmonized standard	EN 1504-2:2004
	Notified body/ies:	The notified body, <b>DEDAL</b> Attestation & Certification, Bulgaria, 8230 Nesebar Mladost #50, with certification no. 1922, carried out the initial inspection of the factory and the production control at the factory and conducts continuous monitoring, evaluation, and approval of the production control under system 2+ and issued:
		Certificate of Conformity of the production control at the factory No. 1922-CPR-0386
6b.	European assessment document:	
	European technical assessment:	
	Technical assessment body:	
	Notified body/ies:	



CONSTRUCTION CHEMICALS SINCE 1959

HEADQUARTERS - PLANT V. Moira str., Xiropigado LOGISTICS & SALES CENTER Loutsas str., Voro P.O. Box 2315, GR 19600 Industrial Area Mandra Athens, Greece T. +30 210 5557579

NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece T. +30 2310 467275

www.neotex.gr • export@neotex.gr

### Declaration of Performance - DoP No.: 4950-12

# Silatex<sup>®</sup> Super

CE

#### 7. Declared performance/s:

Performance	Harmonized technical specification
Class I	
≥1.5N/mm <sup>2</sup>	
$M < 0.1 K g / m^2 h 0.5$	EN 1504-2:2004
W<0.1Kg/11-11-0	
S <sub>D</sub> >50m	
Euroclass F	-
Complies with 5.3	
	Class I ≥1.5N/mm <sup>2</sup> W<0.1Kg/m <sup>2</sup> h <sup>0.5</sup> S <sub>D</sub> >50m Euroclass F

#### 8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX AEVE BRANCH: LOUTSAS STR, THESI VORO, 19500, INDUSTRIAL AREA MANDRA GREECE HEADQUARTERS: V.MOIRA STR, 4000 INDUSTRIAL AREA MANDRA GREECE TEL.: +302105557579 - 1302105246826 - FAX: +30 2105558482 VAT: EL 094029045 - PRN: 4164 www.neotex.gr e-mail: export@neotex.gr

Lampros Ntoumos

**Technical Director** 

NEOTEX/AEVE BRANCH: LOUTSAS STR, THESI VORO, 19607-NOUSTRIAL AREA MANDRA GREECE HEADQUARTERS: V.MOIRA STE, 19607NDUSTRIAL AREA MANDRA GREECE TEL.: +302105557579 · +302105246826 · FAX: +30 2105558482 VAT: EL 094029945 - PRN: 4164 www.neotex.gr e-mail: export@neotex.gr

Marios Bougiouk-Ioannidis

R&D Director



CONSTRUCTION CHEMICALS SINCE 1959

**HEADQUARTERS - PLANT** V. Moira str., Xiropigado LOGISTICS & SALES CENTER Loutsas str., Voro

Industrial Area Mandra Athens, Greece T. +30 210 5557579

P.O. Box 2315, GR 19600 | NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece **T.** +30 2310 467275

www.neotex.gr • export@neotex.gr

(	(			
(	E			
	_			
1	1922			
NEOTEX S.A.				
V.Moira str., P.O. Box 2315				
GR 19600 Industrial Are	ea Mandra, Athens, Greece			
	15			
1922-CPR-0386				
DoP No.: 4950-12				
EN 1504-2				
Silatex <sup>®</sup> Super				
Surface protection products				
Coating				
Water vapour permeability	Class I			
Adhesion strength	≥1.5N/mm <sup>2</sup>			
Capillary absorption and permeability				
to water	W<0.1Kg/m <sup>2</sup> h <sup>0.5</sup>			
Permeability to CO <sub>2</sub>	S <sub>D</sub> >50m			
Reaction to fire	Euroclass F			
Dangerous substances	Complies with 5.3			
Declarations of I	Performance (DoPs)			



3/3