

Proflex[®]

Acrylic coating for exterior use

Description of the product

Premium quality, acrylic, water-based coating suitable for decorating and protecting the exterior surface of any building, applied on concrete and plasters.

Properties

- **Proflex[®]** is applied easily and dries quickly.
- It has great coverage, high spreading rate and strong adhesion.
- It stabilizes and protects the surface.
- The product is particularly durable against industrial pollution and adverse weather conditions.
- It offers vivid colours, complies with stringent specifications concerning artificial weathering and water permeability (8269/1426) and it is environmentally friendly.

Technical Characteristics

Density	1,49g/cm ³
Consumption	10-12m ² /L for one coat depending on substrate porosity.
Drying time (+25°C)	1 hour
Dry to recoat (+25°C)	3 hours
Application temperature	From +8°C to +35°C

Instruction for use

Surface preparation: The substrate should be clean, dry and free from dust, oil, grease, or any poorly adhering material. Remove any flaking coating or severely weathered plaster that may be present and fill any cracks or holes. Before application, it is advisable to prime the surface with **Vinyfix[®] Primer** or copolymer emulsion **Revinex[®]** diluted with water (ratio **Revinex[®]**: water-1:4), in order to seal any pores, fix the substrate, and thus attain better adhesion and higher spreading rates. Apply two coats of **Proflex[®]** by brush, roller or spray gun. Dilute the product with water 10% for the first coat and 5% for the second.

Notes

- Low temperatures and high humidity prolong drying and overcoating times.
- Do not use the product in wet conditions (e.g. high humidity or rain)
- Apply the second coat when the first one has dried completely

Packing

10lt, 3lt and 1lt in plastic containers



ATHENS: V. MOIRA, INDUSTRIAL AREA MANDRA, 19600, ATHENS, GREECE, TEL.:+30 210 5557579, FAX: +30 210 5558482

THESSALONIKI: 10th km N.R THESSALONIKIS-POLIGIROU, 57001, THERMI THESSALONIKI, GREECE, TEL.:+30 2310 467275, FAX: 2310 463442

Proflex[®]

Colours	White, tailor-made shades (upon special arrangement)
Cleaning of tools	Use plenty of water immediately after application.
Storage stability	The product is stable for 2 years when kept unopened in its original container, protected from frost and direct sunlight.

