

## Neosil<sup>®</sup> Bond

### Adhesion promoter for coating systems on inorganic surfaces

---

#### Description of the product

**Neosil<sup>®</sup> Bond** is a solvent-based adhesion promoter that activates the adhesion of primers and coatings on inorganic surfaces, like ceramic tiles and glass. It provides excellent adhesion for the coating system (primer and topcoat) that follows.

---

#### Properties

- Facilitates the excellent adhesion of coatings
- Easy application
- Fast drying

---

#### Technical Characteristics

<b>Appearance</b>	Transparent
<b>Density</b>	0,80±0,05g/cm <sup>3</sup>
<b>Consumption</b>	50ml/m <sup>2</sup> (1layer)
<b>Drying Time (25°C)</b>	15-20 min
<b>Waiting Time for applying coating on top (25°C)</b>	2-24 hours

---

#### Instructions for use / Application notes

The surface must be free of dust, organic substances and oil. The surface must be cleaned with a soft cloth (which must be changed frequently) with **Neosil<sup>®</sup> Bond**. It is necessary to apply the material carefully on the entire surface without leaving untreated spots. 2 hours after drying, the subsequent coating system can be applied. The optimum adhesion results are obtained between 2 - 6 hours. Should more than 24 hours pass from the application, then the whole procedure must be repeated.

---

#### Cleaning of tools

Immediately after application with solvent **Neotex<sup>®</sup> 1021**

---

#### Storage stability

1 year if kept unopened in its original closed package, protected from frost and sunlight

---

#### Packing

1lt

---