

Proflex®

Acrylic coating for interior and exterior use

Description of the product	Acrylic coating for interior and exterior use
Properties	<ul style="list-style-type: none"> • Stabilizes, protects, and decorates walls and facades, providing vivid and stable colour shades • Exceptional resistance to solar radiation and adverse weather conditions • Durable against air pollution • Vapour permeable, allows the walls to "breathe" • High coverage - easy to apply • Fast drying • Eco-friendly & user friendly (water-based, one component)
Technical Characteristics	
Density	1,49g/cm ³
Consumption	10-12m ² /L for one coat depending on substrate porosity.
Drying time (+25°C)	1 hour
Dry to recoat (+25°C)	3 hours
Application temperature	From +8°C to +35°C
Instruction for use	<p>Surface preparation: The substrate should be clean, dry and free from dust, oil, grease, or any poorly adhering material. Remove any flaking coating or severely weathered plaster that may be present and fill any cracks or holes. Before application, it is advisable to prime the surface with Vinyfix® Primer or copolymer emulsion Revinex® diluted with water (ratio Revinex®: water-1:4), in order to seal any pores, fix the substrate, and thus attain better adhesion and higher spreading rates. Apply two coats of Proflex® by brush, roller or spray gun. Dilute the product with water 10% for the first coat and 5% for the second.</p>
Notes	<ul style="list-style-type: none"> • Low temperatures and high humidity prolong drying and overcoating times. • Do not use the product in wet conditions (e.g. high humidity or rain) • Apply the second coat when the first one has dried completely
Packing	10lt, 3lt and 1lt in plastic containers
Colours	White, tailor-made shades (upon special arrangement)



ATHENS: V. Moira str., P.O. Box 2315, GR 19600 Industrial Area Mandra, Athens, Greece, Tel.: +30 210 5557579, Fax: +30 210 5558482
THESSALONIKI: Ionias Str., GR 57009 Kalochori, Thessaloniki, Greece, Tel.: +30 2310 467275, Fax: +30 2310 463442

Proflex[®]

Cleaning of tools

Use plenty of water immediately after application.

Storage stability

The product is stable for 2 years when kept unopened in its original container, protected from frost and direct sunlight.



The information supplied in this datasheet, concerning the uses and the applications of the product, is based on the experience and knowledge of NEOTEX[®] SA. It is offered as a service to designers and contractors in order to help them find potential solutions. However, as a supplier, NEOTEX[®] SA does not control the actual use of the product and therefore cannot be held responsible for the results of its use. As a result of continual technical evolution, it is up to our clients to check with our technical department that this present data sheet has not been modified by a more recent edition.