

HEADQUARTERS - PLANT V. Moira str., Xiropigado LOGISTICS & SALES CENTER Loutsas str., Voro

Industrial Area Mandra Athens, Greece T. +30 210 5557579 T. +30 2310 467275

P.O. Box 2315, GR 19600 | NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece

www.neotex.gr • export@neotex.gr

CONSTRUCTION CHEMICALS SINCE 1959

Declaration of Performance - DoP No.: 4951-05

Neodur® Floor SF



1.	Unique identification code of the product type:	Neodur® Floor SF
2.	Intended use/es:	Surface protection products - Coating
3.	Manufacturer:	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece
4.	Authorized representative:	
5.	System/s of Assessment and Verification of Constancy of Performance (AVCP):	2+
6a.	Harmonized standard	EN 1504-2:2004
	Notified body/ies:	The notified body, DEDAL Attestation & Certification, Bulgaria, 8230 Nesebar Mladost #50, with certification no. 1922, carried out the initial inspection of the factory and the production control at the factory and conducts continuous monitoring, evaluation, and approval of the production control under system 2+ and issued:
		Certificate of Conformity of the production control at the factory No. 1922-CPR-0386
6b.	European assessment document:	
	European technical assessment:	
	Technical assessment body:	
	Notified body/ies:	



CONSTRUCTION CHEMICALS SINCE 1959

HEADQUARTERS - PLANT V. Moira str., Xiropigado LOGISTICS & SALES CENTER Loutsas str., Voro

Industrial Area Mandra Athens, Greece T. +30 210 5557579

P.O. Box 2315, GR 19600 | NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece T. +30 2310 467275

www.neotex.gr • export@neotex.gr

Declaration of Performance - DoP No.: 4951-05

Neodur® Floor SF



7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Water vapour permeability	Class II	
Adhesion strength	≥1.5N/mm ²	
Capillary absorption and permeability to water	W<0.1Kg/m ² h ^{0.5}	EN 1504-2:2004
Permeability to CO ₂	S _D >50m	
Reaction to fire	B _{fl} -s1	
Dangerous substances	Complies with 5.3	

Appropriate technical documentation and/or special technical documentation 8.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX AEVE BRANCH LOUTSAS STR., THESI VOND. 19600. INCHSTRIAL AREA MANDRA GREECE HEADQUARTERS: V.MOIRA STR. 18600 INDUSTRIAL AREA MANDRA GREECE TEL.: +302105557578 - +302105245826. FAX: +30 2105558482 VAT: EL 094029045 - PRN: 4164 www.neotex.gr e-mail: export@neotex.gr

> **Lampros Ntoumos** Technical Director

BRANCH: LOUTSAS STR., THESI VORO., 19600 - INDUSTRIAL AREA MANDRA GREECE HEADQUARTERS: V.MÓIRA STR., 19900 INDUSTRIAL AREA MANDRA GREECE TEL.: +302105557579 · +302105245826 · FAX: +30 2105558482 VAT: EL 094029945 - PRN: 4164 www.neotex.gr e-mail: export@neotex.gr

> Marios Bougiouk-Ioannidis R&D Director



CONSTRUCTION CHEMICALS SINCE 1959

HEADQUARTERS - PLANT V. Moira str., Xiropigado **LOGISTICS & SALES CENTER** Loutsas str., Voro

Industrial Area Mandra Athens, Greece T. +30 210 5557579

P.O. Box 2315, GR 19600 | NORTHERN GREECE BRANCH Ionias str., GR 57009 Kalochori Thessaloniki, Greece T.+30 2310 467275

www.neotex.gr • export@neotex.gr

1922

NEOTEX S.A.

V.Moira str., P.O. Box 2315 GR 19600 Industrial Area Mandra, Athens, Greece

24

1922-CPR-0386

DoP No.: 4951-05

EN 1504-2

Neodur® Floor SF

Surface protection products

Coating

Water vapour permeability	Class II	
Adhesion strength	≥1.5N/mm ²	
Capillary absorption and permeability	W<0.1Kg/m ² h ^{0.5}	
to water		
Permeability to CO ₂	S _D >50m	
Reaction to fire	B _{fl} -s1	
Dangerous substances	Complies with 5.3	

Declarations of Performance (DoPs)



