

# N-Thermon® Primer

## Strong bonding quartz sand primer

### Description

Strong bonding quartz sand primer, with fine and medium quartz sand, ideal for the adhesion improvement of mortars on smooth substrates.  
Part of **N-Thermon® System**.

### Fields of application

- As part of the **N-Thermon® System**, acting as a bridge of adhesion between **N-Thermon®** insulation boards and plaster **Deplast®**
- On smooth surfaces, such as exposed concrete, cement boards, gypsum boards and polystyrene sheets, for enhancing the adhesion of succeeding plasters, mortars, tile adhesives, cement screeds etc.
- Over surfaces painted with acrylic-emulsion paints, as an adhesion bridge

### Properties - Advantages

- Very strong adhesion on smooth and non-absorbent surfaces
- May be overcoated even after several days have passed from its application
- Resistant to the alkalis of cement
- Suitable for interior and exterior use
- Ready to use and easy to apply.



### Colours

WHITE

SALMON

### Packing

15kg, 5kg and 1kg

### Technical characteristics

Density (EN ISO 2811-1)	1,32kg/L (±0,1)
pH (ISO 1148)	8-9

**Consumption: 200-350 gr/m<sup>2</sup> in one layer (depending on the absorptivity of the substrate)**

### Application conditions

Substrate moisture content	<4%
Relative air humidity (RH)	<70%
Application temperature (ambient - substrate)	+10°C min. / +35°C max.



### Curing details

Drying time (+25°C, RH 50%)	3 hours
Dry to overcoat (+25°C, RH 50%)	24 hours

*\* Low temperatures and high humidity during application and/or curing prolong the above times, while high temperatures reduce them*

### Instructions for use

#### **Substrate preparation**

The surface must be stable, clean, dry, protected from rising moisture and free of dust, oil, grease and loose materials. Any loose materials and older coatings must be removed carefully by proper mechanical or chemical means.

#### **Application**

After thorough stirring, **N-Thermon® Primer** is applied, undiluted, on the smooth and non-absorbent substrate, by roller or brush, in one thin layer.

### Special notes

- **N-Thermon® Primer** should not be applied under wet conditions, or if wet conditions are expected to prevail during the application or the curing period of the product.
- If needed, **N-Thermon® Primer** may be diluted up to 3% with water.

<b>Appearance</b>	Viscous liquid
<b>Colour</b>	White and salmon
<b>Packing</b>	15kg, 5kg and 1kg in plastic pails
<b>Cleaning of tools – Stains removal</b>	By water immediately after the application. In case of hardened stains, by mechanical means only.
<b>Volatile organic compounds (V.O.C.)</b>	V.O.C. limit acc. to the E.U. Directive 2004/42/CE for this product of category AgWB: 30g/l (Limit 1.1.2010) - V.O.C. content of the ready-to-use product <30g/l
<b>UFI code</b>	58C0-JOPE-000Y-GT3J
<b>Storage stability</b>	1 year, if kept in the original sealed packaging, protected from frost, humidity and exposure to solar radiation.



The information supplied in this datasheet, concerning the uses and the applications of the product, is based on the experience and knowledge of NEOTEX® SA. It is offered as a service to designers and contractors to help them find potential solutions. However, as a supplier, NEOTEX® SA does not control the actual use of the product and therefore cannot be held responsible for the results of its use. As a result of continual technical evolution, it is up to our clients to check with our technical department that this present data sheet has not been modified by a more recent edition.

**HEADQUARTERS - PLANT**  
V. Moira str., Xiropigado  
**LOGISTICS SALES & CENTER**  
Loutsas str., Voro

P.O. Box 2315, GR 19600  
Industrial Area Mandra  
Athens, Greece  
T. +30 210 5557579

**NORTHERN GREECE BRANCH**  
Ionias str., GR 57009  
Kalochori, Thessaloniki, Greece  
T. +30 2310 467275

[www.neotex.gr](http://www.neotex.gr) ● [export@neotex.gr](mailto:export@neotex.gr)