

Neotex® 1111

Special thinner for primers and coatings

Description

Special thinner suitable for the acrylic primer **Silatex® Primer**, as well as for the dilution of alkyd-based paints.

Also suitable for the cleaning of the surfaces or tools after the application of the above products.



Packing

5L and 1L

Technical Characteristics

Density (EN ISO 2811-1)	0,80kg/L (±0,05)
-------------------------	------------------

Appearance	Transparent
------------	-------------

Packing	5L and 1L in metal cans
---------	-------------------------

UFI code	12A0-G00U-R002-70XN
----------	---------------------

Storage stability	2 years, stored in its original sealed packing, protected from frost, humidity and exposure to sunlight
-------------------	---

The information supplied in this datasheet, concerning the uses and the applications of the product, is based on the experience and knowledge of NEOTEX® SA. It is offered as a service to designers and contractors to help them find potential solutions. However, as a supplier, NEOTEX® SA does not control the actual use of the product and therefore cannot be held responsible for the results of its use. As a result of continual technical evolution, it is up to our clients to check with our technical department that this present data sheet has not been modified by a more recent edition

HEADQUARTERS - PLANT
V. Moira str., Xiropigado
LOGISTICS SALES & CENTER
Loutsas str., Voro

P.O. Box 2315, GR 19600
Industrial Area Mandra
Athens, Greece
T. +30 210 5557579

NORTHERN GREECE BRANCH
Ionias str., GR 57009
Kalochori, Thessaloniki, Greece
T. +30 2310 467275