

Declaration of Performance - DoP No.: 4950-32

Deplast®



1. Unique identification code of the product type:	Deplast®	
2. Intended use/es:	General purpose rendering mortar (GP) for interior and exterior use	
3. Manufacturer:	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece (Production factory 2)	
4. Authorized representative:	---	
5. System/s of Assessment and Verification of Constancy of Performance (AVCP):	4	
6a. Harmonized standard	EN 998-1	
Notified body/ies:	---	
6b. European assessment document:	---	
European technical assessment:	---	
Technical assessment body:	---	
Notified body/ies:	---	
7. Declared performance/s:		
Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1	EN 13813
Compressive strength	CS IV	
Adhesion	≥1N/mm ² – FP B	
Water absorption	W2	
Water vapour diffusion coefficient	μ≤765	
Thermal conductivity λ _{10,dry,mat}	0,45 W/mK (tabulated value)	
Durability	Complies to 5.3.2	

Declaration of Performance - DoP No.: 4950-32

Deplast®



8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX AEVE
BRANCH: LOUTSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Lampros Ntoumos
Technical Director

NEOTEX AEVE
BRANCH: LOUTSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Marios Bougiouk-loannidis
R&D Director

CE	
<p>NEOTEX S.A. V.Moira str., P.O. Box 2315 GR 19600 Industrial Area Mandra, Athens, Greece (Production factory 2)</p> <p>13</p>	
<p>DoP No.: 4950-32</p> <p>EN 998-1 GP-CS IV-W2</p> <p>Deplast®</p> <p>General purpose rendering mortar (GP) for interior and exterior use</p>	
Reaction to fire	A1
Compressive strength	CS IV
Adhesion	≥1N/mm ² – FP B
Water absorption	W2
Water vapour diffusion coefficient	μ≤765
Thermal conductivity λ _{10,dry,mat}	0,45 W/mK (tabulated value)
Durability	Complies to 5.3.2
<p><u>Declarations of Performance (DoPs)</u></p>	

