

Declaration of Performance - DoP No.: 4950-44

Epoxol® 3D



1. Unique identification code of the product type:	Epoxol® 3D	
2. Intended use/es:	Synthetic Resin screed material for use internally in buildings	
3. Manufacturer:	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece	
4. Authorized representative:	---	
5. System/s of Assessment and Verification of Constancy of Performance (AVCP):	4	
6a. Harmonized standard	EN 13813	
Notified body/ies:	---	
6b. European assessment document:	---	
European technical assessment:	---	
Technical assessment body:	---	
Notified body/ies:	---	
7. Declared performance/s:		
Essential characteristics	Performance	Harmonized technical specification
Release of corrosive substances	SR	EN 13813
Compressive strength	C60	
Flexural strength	F50	
Wear resistance	RWA20	
Hardness	SH50	
Impact resistance	IR4	
Bond strength	B2,0	
Reaction to fire	NPD	

Declaration of Performance - DoP No.: 4950-44

Epoxol® 3D



8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX AEVE
BRANCH: LOUTSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Lampros Ntoumos
Technical Director

NEOTEX AEVE
BRANCH: LOUTSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Marios Bougiouk-loannidis
R&D Director



NEOTEX S.A.
V.Moira str., P.O. Box 2315
GR 19600 Industrial Area Mandra, Athens, Greece

19

DoP No.: 4950-44

EN 13813 SR-C60-F50-RWA20-SH50-B2,0-IR4

Epoxol® 3D

Synthetic resin screed material for use internally in buildings

Release of corrosive substances	SR
Compressive strength	C60
Flexural strength	F50
Wear resistance	RWA20
Hardness	SH50
Impact resistance	IR4
Bond strength	B2,0
Reaction to fire	NPD

[Declarations of Performance \(DoPs\)](#)

