

## Declaration of Performance - DoP No.: 4950-36

# Neodur<sup>®</sup> FT Elastic



<b>1. Unique identification code of the product type:</b>	Neodur <sup>®</sup> FT Elastic
<b>2. Intended use/es:</b>	Surface protection products – Coating
<b>3. Manufacturer:</b>	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece
<b>4. Authorized representative:</b>	---
<b>5. System/s of Assessment and Verification of Constancy of Performance (AVCP):</b>	2+
<b>6a. Harmonized standard</b>	EN 1504-2:2004
<b>Notified body/ies:</b>	The notified body, <b>DEDAL Attestation &amp; Certification, Bulgaria, 8230 Nesebar Mladost #50</b> , with <i>certification no. 1922</i> , carried out the initial inspection of the factory and the production control at the factory and conducts continuous monitoring, evaluation, and approval of the production control under system 2+ and issued:  <b><i>Certificate of Conformity of the production control at the factory No. 1922-CPR-0386</i></b>
<b>6b. European assessment document:</b>	---
<b>European technical assessment:</b>	---
<b>Technical assessment body:</b>	---
<b>Notified body/ies:</b>	---

## Declaration of Performance - DoP No.: 4950-36

# Neodur<sup>®</sup> FT Elastic



### 7. Declared performance/s:

Essential characteristics	Performance	Harmonized technical specification
Water vapour permeability	Class II	<b>EN 1504-2:2004</b>
Adhesion strength	≥1.5N/mm <sup>2</sup>	
Capillary absorption and permeability to water	W<0.1Kg/m <sup>2</sup> h <sup>0.5</sup>	
Permeability to CO <sub>2</sub>	S <sub>D</sub> >50m	
Reaction to fire	Euroclass F	
Dangerous substances	Complies with 5.3	

### 8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

**NEOTEX A EVE**  
BRANCH: LOUSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE  
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE  
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482  
VAT: EL 094029945 - PRN: 4164  
www.neotex.gr e-mail: export@neotex.gr

*Lampros Ntoumos*  
Technical Director

**NEOTEX A EVE**  
BRANCH: LOUSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE  
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE  
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482  
VAT: EL 094029945 - PRN: 4164  
www.neotex.gr e-mail: export@neotex.gr

*Marios Bougiouk-Ioannidis*  
R&D Director

 1922	
<b>NEOTEX S.A.</b> V.Moira str., P.O. Box 2315 GR 19600 Industrial Area Mandra, Athens, Greece  19	
1922-CPR-0386  DoP No.: 4950-36  <b>EN 1504-2</b>  <b>Neodur® FT Elastic</b>  Surface protection products  Coating	
Water vapour permeability	Class II
Adhesion strength	≥1.5N/mm <sup>2</sup>
Capillary absorption and permeability to water	W<0.1Kg/m <sup>2</sup> h <sup>0.5</sup>
Permeability to CO <sub>2</sub>	S <sub>D</sub> >50m
Reaction to fire	Euroclass F
Dangerous substances	Complies with 5.3
<a href="#"><u>Declarations of Performance (DoPs)</u></a>	

