

Declaration of Performance - DoP No.: 4950-42

Neofloor®



1. Unique identification code of the product type:	Neofloor®	
2. Intended use/es:	Cementitious screed material for floors	
3. Manufacturer:	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece (Production factory 2)	
4. Authorized representative:	---	
5. System/s of Assessment and Verification of Constancy of Performance (AVCP):	4	
6a. Harmonized standard	EN 13813	
Notified body/ies:	---	
6b. European assessment document:	---	
European technical assessment:	---	
Technical assessment body:	---	
Notified body/ies:	---	
7. Declared performance/s:		
Essential characteristics	Performance	Harmonized technical specification
Release of corrosive substances	CT	EN 13813
Compressive strength	C50	
Flexural strength	F10	
Wear resistance	A9	
Bond strength	B1,5	
Reaction to fire	A1	

Declaration of Performance - DoP No.: 4950-42

Neofloor®



8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX AEVE
BRANCH: LOUTSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Lampros Ntoumos

Technical Director

NEOTEX AEVE
BRANCH: LOUTSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Marios Bougiouk-loannidis

R&D Director

CE	
<p>NEOTEX S.A. V.Moira str., P.O. Box 2315 GR 19600 Industrial Area Mandra, Athens, Greece (Production factory 2)</p> <p>19</p>	
<p>DoP No.: 4950-42</p> <p>EN 13813 CT-C50-F10-A9-B1,5</p> <p>Neofloor®</p> <p>Cementitious screed material for floors</p>	
Release of corrosive substances	CT
Compressive strength	C50
Flexural strength	F10
Wear resistance	A9
Bond strength	B1,5
Reaction to fire	A1
<p><u>Declarations of Performance (DoPs)</u></p>	

