

Declaration of Performance - DoP No.: 4951-14

Neopox[®] W Plus



1. Unique identification code of the product type:	Neopox[®] W Plus	
2. Intended use/es:	Synthetic Resin screed material for use internally in buildings	
3. Manufacturer:	NEOTEX S.A., V. Moira, 19600 Industrial Area Mandra, Greece	
4. Authorized representative:	---	
5. System/s of Assessment and Verification of Constancy of Performance (AVCP):	4	
6a. Harmonized standard	EN 13813	
Notified body/ies:	---	
6b. European assessment document:	---	
European technical assessment:	---	
Technical assessment body:	---	
Notified body/ies:	---	
7. Declared performance/s:		
Essential characteristics	Performance	Harmonized technical specification EN 13813
Release of corrosive substances	SR	
Wear resistance	AR1	
Impact resistance	IR5	
Bond strength	B2,0	
Reaction to fire	Bfl-s1	

Declaration of Performance - DoP No.: 4951-14

Neopox® W Plus



8. Appropriate technical documentation and/or special technical documentation

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

NEOTEX AEVE
BRANCH: LOUSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Lampros Ntoumos

Technical Director

NEOTEX AEVE
BRANCH: LOUSAS STR, THESI VORO, 19600 - INDUSTRIAL AREA MANDRA GREECE
HEADQUARTERS: V.MOIRA STR., 19600 INDUSTRIAL AREA MANDRA -GREECE
TEL.: +302105557579 - +302105246826 - FAX: +30 2105558482
VAT: EL 094029945 - PRN: 4164
www.neotex.gr e-mail: export@neotex.gr

Marios Bougiouk-Ioannidis

R&D Director



NEOTEX S.A.
V.Moira str., P.O. Box 2315
GR 19600 Industrial Area Mandra, Athens, Greece

24

DoP No.: 4951-14

EN 13813 SR-AR1-B2,0-IR5

Neopox® W Plus

Synthetic Resin screed material for use internally
in buildings

Release of corrosive substances	SR
Wear resistance	AR1
Impact resistance	IR5
Bonding strength	B2,0
Reaction to fire	Bfl-s1

[Declarations of Performance \(DoPs\)](#)

