



Neobond® Primer

Description of the product	Strong bonding quartz sand primer, with medium and coarse quartz sand, for adhesion improvement of cement mortars on smooth substrates
Fields of applications	<ul style="list-style-type: none"> ➤ On smooth surfaces, such as concrete, cement boards, gypsum boards, polystyrene sheets, for enhancing the adhesion of succeeding cementitious mortars, plasters, tile adhesives etc. ➤ Applicable also over painted surfaces (with emulsion paints), as an adhesion bridge
Properties – Advantages	<ul style="list-style-type: none"> ➤ Remarkable adhesion on smooth substrates ➤ May be overcoated by cement mortars even after several days have passed from its application ➤ Alkali resistant ➤ Suitable for interior and exterior use
Technical characteristics	
Appearance	viscous liquid
Color	Light Green
Density (ISO 8962, DIN 51757)	1,39 g/cm ³
pH (ISO 1148, DIN 53785)	8-9
Consumption	330-400gr/m ²
Touch dry (25°C)	3 hours
Time to cover with cement mortars (25°C)	after 24 hours
Instruction for use	Neobond® Primer is applied with brush, roller. After thorough cleaning and removal of loose particles and dust, apply 1 layer of the product. The application of cement mortar can take place after 24 hours, without further limitations on the time it will take place.
Precautions	<ul style="list-style-type: none"> ➤ Neobond® Primer must NOT be applied below +10°C ➤ Applied undiluted, or with a slight dilution (maximum 3%) with water.
Packing	5 kg and 15 kg in plastic containers
Cleaning of Tools	Use plenty of water immediately after application
Stain removal	Use water when the stain is still fresh and damp. In case of hardened stains, use mechanical means or a paint remover.

Neobond[®] Primer

Safety Precautions

See Safety Data Sheets

Storage Stability

12 months stored in its initial, sealed packing, at +5°C to +35°C, protected from sunlight and frost

